Kodak EasyShare zoom digital camera

cx7525

Amazing picture quality

- Get amazing-quality prints up to 20" x 30" with 5.0 MP
- Capture crisp details with the aspheric, all-glass Kodak Retinar 3X optical zoom lens
- Get even closer to your subject with 5X advanced digital zoom
- Multi-zone auto-focus with enhanced low-light performance for razor-sharp pictures
- Achieve breathtaking color under a variety of lighting conditions with the Kodak color science image processing chip

Incredible ease of use

- Easy-to-access scene and color modes for consistently great pictures
- Catch all the action with TV-quality (VGA) video featuring audio playback
- See your vertical shots vertically with auto picture rotation
- Compatible with Kodak EasyShare camera and printer docks*
- Get started right away with its 16 MB internal memory

The simple way to share

- Print, e-mail, and organize your photos with just one touch of the exclusive Share button
- Review your pictures on the bright, 1.6" indoor/outdoor display
- On-camera Favorites feature to share your pictures anytime, anywhere
- Print directly from your camera to any PictBridge enabled printer

It's the advanced camera without the complicated attitude. Introducing the Kodak EasyShare CX7525 zoom digital camera. It's built to deliver exceptional-quality photos with point-and-shoot simplicity. But it's what happens after you take your pictures that you'll find most amazing. Just press the on-camera Share button for one-touch-simple picture sharing. With the CX7525, the only thing simpler than taking a great picture is sharing it.

Just press share™

5.0 MEGAPIXEL | 20" 30" 50x75cm MAX PRINT SIZE | 3X OPTICAL ZOOM 5X ADVANCED DIGITAL 15X TOTAL ZOOM | SHARE BUTTON | FAVORITES | MULTI SCENE MODES | VIDEO/AUDIO | LOW LIGHT AUTO FOCUS | INDOOR/OUTDOOR DISPLAY | AUTO PICTURE ROTATION | 16MB INTERNAL MEMORY | COMPATIBLE WITH *EASYSHARE* DOCKS | PictBridge *PICTBRIDGE* ENABLED

Making digital even simpler

The optional Kodak EasyShare printer dock is the simplest way to go from picture to print. Just dock your Kodak EasyShare digital camera, touch the button, and get real Kodak borderless 4" x 6" prints. It even works with or without a computer. And just like the optional Kodak EasyShare camera dock 6000, the printer dock transfers pictures from camera to computer at the touch of a button and recharges your Kodak camera battery in less than 3.5 hours**.

CX7525

Standard Features

CCD – 1/2.5 inch type (5.36 M total pixels)
Effective pixels – 5.0 megapixels (2560x1920 pixels)
Picture quality
- 5.0 MP – best (prints up to 20" x 30")
- 4.4 MP – best 3:2 (optimized ratio for 4" x 6" prints)
- 3.1 MP – better (prints up to 11" x 14")
- 1.7 MP – good (small prints)

Still format JPEG/EXIF v 2.2.1
Lens – 3X optical zoom
- 5.6-16.8 mm (35 mm equivalent: 34-102 mm)

Advanced digital zoom – 5X
Aperture – f/2.7-5.2 (wide), f/4.6-8.7 (tele)
Shutter speed – 1/2-1/1400 sec.
Real image optical viewfinder
LCD – 1.6" (4 cm) indoor/outdoor color display

Performance Features

Scene modes – auto, portrait, landscape, night, close-up, sport, movie
Photo settings – color, black and white, sepia
Burst mode – 2.4 fps, up to 5 pictures
Click to capture – 0.6 sec.
Shot to shot – 1.3 sec.
Video mode – continuous MPEG-4 video with audio capture/playback
Video resolution – VGA (640x480 pixels) at 13 fps; QVGA (320x240 pixels) at 20 fps
Video length – continuous up to 80 min. limited by capacity of external memory card; or 5, 15, 30 sec. clips
Video format – Quicktime MOV (MPEG-4 compression)
Auto focus – TTL-AF
Auto focus selection – multi-zone, center-zone
Focus range
- Standard – 60 cm (23.6 in.) to infinity
- Landscape – 0.6 m (2 ft.) to infinity
- Close-up wide – 13-70 cm (5-28 in.)
- Close-up tele – 22-70 cm (9-28 in.)

Sensitivity – ISO equivalent 80-160 (automatic) and 80,100, 200, 400 (manual)
White balance – auto, daylight, tungsten, fluorescent
Exposure metering – TTL-AE; selectable: multi-pattern, center-weighted, center spot
Exposure control – programmed AE
Long time exposure – 0.7-4 sec.
Exposure compensation – +/-2.0 EV in 0.5 EV step increments

Ease of Use Features

Built-in flash – auto, red-eye, fill, off
Flash range
- wide – 0.6-3.6 m (2-11.8 ft.)
- tele – 0.6-2.1 m (2-6.9 ft.)

Review options – 1X–8X magnify with pan, slide show, multi-up, fast scroll, protect, album
Favorites – on-camera picture storage
Auto picture rotation
Software – Kodak EasyShare software
Dock compatibility – Kodak EasyShare camera docks, Kodak EasyShare printer docks*
PictBridge compatible – print directly from camera
Storage – 16 MB internal memory, SD/MMC card expansion slot
Self-timer – 10 seconds

Additional Features

Power options – optional Kodak EasyShare docks with Ni-MH rechargeable battery pack; 2 AA Kodak Max digital camera batteries; 2 AA lithium or Ni-MH batteries or 1 CRV3 lithium battery; 3 volt DC
Lens protection – built-in lens barrier
Tripod mount – 1/4 in. standard
I/O interface – power input (3V DC), A/V output (NTSC or PAL, user selectable), Kodak camera dock/printer dock interface, USB compliant connector
Weight – without batteries: 178 g (6.3 oz.)
Dimensions – WxHxD: 102.5x65x38 mm (4.0x2.6x1.5 in.)
Warranty – one year

Minimum System Requirements

Windows 98, 98SE, ME, 2000 SPI, or XP OS
- Internet Explorer 5.01 or higher
- 233 MHz processor or greater

Macintosh OS X 10.2.3, 10.3
- Safari 1.0 or higher

Minimum Hardware Requirements

128 MB RAM (64 MB RAM for Windows 98, 98SE, 2000 SP1, ME OS)
200 MB hard drive disk space available
CD-ROM drive
Available USB port

Package Contents

Kodak EasyShare CX7525 zoom digital camera
Kodak Max digital camera batteries AA or equiv.
Video out cable
USB cable
Wrist strap
Kodak EasyShare software
Getting Started kit
Custom camera insert for optional Kodak EasyShare camera and printer docks

Recommended Accessories

Kodak EasyShare printer dock plus
Kodak color cartridge and photo paper kit
Kodak EasyShare camera dock 6000
Kodak SD memory card, 128 MB
Kodak EasyShare Ni-MH rechargeable battery pack
Kodak EasyShare travel kit
Kodak 8-in-1 card reader

*Compatible with optional Kodak EasyShare printer and camera docks, except printer dock 4000 and camera dock II.
**Actual battery charging time may vary by camera model.

Exif Print | USB UNIVERSAL SERIAL BUS | PictBridge

Kodak Worldwide Sponsor

©Eastman Kodak Company, 2004. Kodak, EasyShare, Max, Retinar, the Share button, and Share Moments. Share Life. are trademarks of Eastman Kodak Company. Product specifications subject to change without prior notice. Simulated images.

Share Moments. Share Life.™

Kodak